

SULLAIR RIVET BUSTERS

POWER FOR CUTTING OFF LARGE RIVET HEADS, HEAVY-DUTY CHIPPING, AND CONCRETE BREAKING. APPLICATIONS INCLUDE BRIDGE JOBS, STEEL STRUCTURE MAINTENANCE, RAILROAD CAR REPAIR, SHIPYARDS, PETROCHEMICAL PLANTS AND DEMOLITION WORK.

D-Handle with Inside Trigger
Handle design provides comfort and control to the operator in demolition applications.

Variable Throttle Control
Allows variable speed control for maximum production.

Muffler and Screened Inlet Bushing Standard
Provides quieter operation and filters the inlet from contaminating particles.

Interchangeable Parts Provide Flexibility
Interchangeable parts (except cylinder) reduce inventory and increase parts versatility.

Simplified Control Valve
Allows for smoother operation in dirty conditions through precisely engineered tolerances.

90-Day Parts Warranty
This Sullair warranty covers all tool parts against manufacturing defects.

Lubrication
Rivet Busters require inline lubrication (option).



For use on concrete, Sullair offers Chisel and Mail Point Steels for its Rivet Busters. 11X Jumbo is standard.

MRB-8 & MRB-11 RIVET BUSTER DESIGN SPECIFICATIONS

Model	MRB-8	MRB-11
Net Weight	30 lbs.	33 lbs.
Length	22½"	25½"
Shipping Weight	35 lbs.	38 lbs.
Bore and Stroke	1¾" X 8"	1¾" X 11"
Blows per Minute	1140	850
Air Consumption	44 cfm	50 cfm
Air Inlet	½" NPT	½" NPT
Chuck Size	11X Jumbo	11X Jumbo



MRB-8

MRB-11